



Furlong Flooring®
First choice flooring for every room

RIVER PRODUCT SPECIFICATION

PRODUCT INFORMATION	PRODUCT SPECIFICATION	
Collection	River	
Thickness	8mm	EN 13329+A2
Width	197mm	EN 13329+A2
Length	1205mm	EN 13329+A2
Surface	Authentic	
Quantity/weight per box (PU)	8 pieces = 1.9m ² /approx 14 kg	
Quantity/weight per pallet	56 PU= 106.4 m ² /approx 810 kg	
Class	32	EN13329 + A2
Abrasion Resistance	AC4	EN13329 + A2
Thickness Swelling	≤18	ISO 24336
Surface Swelling (Assembled Joint)	Qualitative Rating ≤2 (1-5) Quantative Rating ≤0,3mm	ISO 4760 (Nalfa 72h)
Resistance to Impact	Small Ball ≥12 N Large Ball ≥750mm	EN 13329+A2
Warranty Domestic/commercial	15/10 Years	
Resistance to Staining	Min.5 (group 1 and 2) Min4. (group 3)	EN 438-2_5
Surface Soundness	≥1.25 N/mm ²	EN 13329+A2
Lock Strength	Length fl0,2 ≥ 1 kN/m Width fs0,2 ≥2 kN/m	ISO 24334
Effect of Castor Chair	25.000 Cycles - No Damage	EN 425:2002
Effect of a Furniture Leg	No Damage	EN 424
Opening Between Elements	≤0,20mm	EN 13329+A2
Height Difference Between Elements	≤0,15mm	EN 13329+A2
Moisture Content	4-10%	EN 322
Fire Resistance	CflS1	EN 9239-1
Formaldehyde Release	E0≤1,75 1,75≤E1≤3,5 mg/m ² h	EN 12460-3
Slip Resistance	DS	EN 14041:2008
Thermal Conductivity	0.148 W/(m*K)	EN 12667:2001
Sound Rating	14dB	ISO 717-2





RIVER PRODUCT SPECIFICATION

COLOURS	ITEM
Danube Oak	FRV001
Tigris Oak	FRV002
Delaware Oak	FRV003
Ganges Oak	FRV004
Thames Oak	FRV005
Nile Oak	FRV006
Trent Oak	FRV007
Erne Oak	FRV008

Bevel

Bevelled on 4 edges.



Water Resistant - up to
72 Hours



Eco friendly flooring.



AC4 - Impact
Resistant



Uni-Click
Fitting



DARTFORD
01322 628700
PRESTON
01772 316155

STONEHOUSE
01452 228480
DUBLIN
+353-1-4092000



Alternatively, visit furlongflooring.com
or email enquiries@furlongflooring.com

Follow us on

